

CT Self-locking Nylon Cable Ties

Material: Nylon 66.94V-2 certificated by UL. Heat-resisting erosion control, insulate well and not apt to age,

Operating temperature: -40°C to 85°C

Color: natural (or white, standard color), UV black and other colors are available as requested

ITEM.NO	L		W(mm)	Bundl diameter (mm)	Min,loop Tensile strength		packing
	INCH	mm			LBS	KGS	
CT3×60	2 3/8"	60	2.5	2-11	18	8	100pcs or 1000pcs/bolt
CT3×80	3 3/16"	80	2.5	2-16	18	8	
CT3×100	4"	100	2.5	2-22	18	8	
CT3×120	4 3/4"	120	2.5	2-30	18	8	
CT3×150	6"	150	2.9	2-35	18	8	
CT3×160	6 1/4"	160	2.5	2-40	18	8	
CT3×200	8"	200	2.5	3-50	18	8	
CT4×140	5 1/2"	140	3.5	3-33	40	18	100pcs or 500pcs/bolt
CT4×150	6"	150	3.5	3-35	40	18	
CT4×180	7"	180	3.8	3-42	40	18	
CT4×200	8"	200	3.5	3-50	40	18	100pcs or 250pcs/bolt
CT4×250	10"	250	3.5	3-60	40	18	
CT4×280	11"	280	3.5	3-70	40	18	
CT4×300	11 5/8"	300	8.5	3-80	40	18	
CT4×370	14 1/2"	370	3.5	3-102	40	18	
CT5×120	4 3/4"	120	4.8	3-42	50	22	100pcs or 500pcs/bolt
CT5×180	7"	180	4.8	3-46	50	22	
CT5×190	7 1/2"	190	4.8	3-46	50	22	100pcs or 200pcs/bolt
CT5×200	8"	200	4.8	3-50	50	22	
CT5×250	10"	250	4.8	3-65	50	22	
CT5×280	10"	280	4.8	3-70	50	22	
CT5×300	11 5/8"	300	4.8	3-82	50	22	
CT5×350	13 3/4"	350	4.8	3-90	50	22	100pcs
CT5×380	15"	380	4.8	3-102	50	22	
CT5×400	15 3/4"	400	4.9	3-105	50	22	
CT5×430	17"	430	4.8	3-110	50	22	100pcs & 250pcs
CT5×450	17 3/4"	450	4.8	3-130	50	22	
CT8×150	6"	150	7.0	3-33	120	55	
CT8×180	7"	180	1.0	3-42	120	55	
CT8×200	8"	200	7.0	3-50	120	55	
CT8×250	10"	250	7.0	4-63	120	55	
CT8×300	11 5/8"	300	7.0	4-82	120	55	
CT8×350	13 3/4"	350	7.9	4-90	120	55	
CT8×400	15 3/4"	400	7.9	4-105	120	55	
CT8×450	17 3/4"	450	7.8	4-108	120	55	
CT8×500	19 11/16"	500	7.9	4-150	120	55	100pcs
CT9×550	21 11/16"	550	9.0	8-160	175	80	
CT9×650	25 9/16"	650	9.0	8-190	175	80	
CT9×760	30"	760	9.0	10-225	175	80	
CT9×920	36 1/4"	920	9.0	10-265	175	80	
CT9×1020	40 1/8"	1020	9.0	10-295	175	80	
CT10×450	17 3/4"	450	10.0	10-125	200	91	
CT10×500	19 11/16"	500	10.0	12-175	200	91	
CT10×600	23 3/2"	600	10.0	12-205	200	91	
CT10×700	27 1/2"	700	10.0	12-205	200	91	
CT12×650	25 9/16"	650	12.0	14-190	250	114	
CT12×750	25 9/16"	750	12.0	10-220	250	114	

