

## HRS Heat Shrinkage Tube

### Function

- 1.Wire coat and insulation.
- 2.Make the joint of terminal block and wire insulated
- 3.Divide the colors
- 4.Water-proff
- 5.Protection and insulation of insistors and electrical capacitors

Standard color:

Black,white,red,blue,yellow,green,brown,grey,orange and purple.

\* Note:higher shrinkage and extention rate are available depend on order.

Type	Before shrinkage		After shrinkage		Packing
	D(mm)	Thickness	1.D(mm)	Thickness	
HRS-1	1.0	0.2±0.05	0.5	0.4±0.05	400
HRS-1.5	1.5	0.2±0.05	0.75	0.4±0.05	300
HRS-2	2.0	0.25±0.05	1.0	0.45±0.1	200
HRS-2.5	2.5	0.25±0.05	1.25	0.45±0.1	
HRS-3	3.0	0.25±0.05	1.5	0.45±0.1	100
HRS-3.5	3.5	0.25±0.05	1.75	0.45±0.1	
HRS-4	4.0	0.25±0.05	2.0	0.45±0.1	
HRS-5	5.0	0.35±0.05	2.5	0.55±0.1	
HRS-6	6.0	0.35±0.05	3.0	0.55±0.1	
HRS-7	7.0	0.35±0.05	3.5	0.55±0.1	
HRS-8	8.0	0.35±0.05	4.0	0.55±0.1	
HRS-9	9.0	0.35±0.05	4.5	0.55±0.1	100
HRS-10	10.0	0.35±0.05	5.0	0.60±0.1	
HRS-11	11.0	6.35±0.05	5.5	0.60±0.1	
HRS-12	12.0	0.35±0.05	6.0	0.70±0.1	50
HRS-13	13.0	0.35±0.1	6.5	0.4±0.05	
HRS-14	14.0	0.35±0.1	7.0	0.4±0.05	
HRS-15	15.0	0.35±0.1	7.5	0.4±0.05	
HRS-16	16.0	0.35±0.1	8.0	0.4±0.05	
HRS-17	17.0	0.35±0.1	8.5	0.4±0.05	25
HRS-18	18.0	0.4±0.1	9.0	0.80±0.1	
HRS-20	20.0	0.5±0.1	10.0	0.90±0.1	
HRS-22	22.0	0.5±0.1	11.0	0.90±0.1	
HRS-25	25.0	0.5±0.1	12.5	0.90±0.1	
HRS-28	28.0	0.5±0.1	14.0	0.90±0.1	
HRS-30	30.0	0.5±0.1	15.0	1.00±0.2	25
HRS-35	35.0	0.5±0.1	17.5	1.00±0.2	
HRS-40	40.0	0.5±0.1	20.0	1.00±0.2	
HRS-50	50.0	0.5±0.1	25.0	1.00±0.2	
HRS-60	60.0	0.6±0.1	30.0	1.20±0.2	
HRS-70	70.0	0.6±0.1	35.0	1.20±0.2	
HRS-80	80.0	6.6±0.1	40.0	1.20±0.2	
HRS-90	90.0	0.6±0.1	45.0	1.30±0.2	
HRS-100	100.0	0.7±0.1	50.0	1.30±0.2	

